

READ SAFETY DIRECTIONS BEFORE OPENING OR USING

TITAN

Wetter 1000

Wetting Agent

ACTIVE CONSTITUENT:
1000g/L ALCOHOL ALKOXYLATES

A bio-degradable spray additive that increases wetting and absorption of herbicides, fungicides and insecticides.

IMPORTANT: READ THOROUGHLY BEFORE OPENING OR USING THIS PRODUCT.

APVMA Approval No.: 50389/0507

Pack Sizes: 5L, 20L



TITAN AG Pty Ltd

15/16 Princes Street, Newport NSW 2106

Tel 02 9999 6655 Fax 02 9999 0483

www.titanag.com.au

IN A TRANSPORT EMERGENCY

DIAL 000

POLICE OR FIRE BRIGADE

TRANSPORT AND HANDLING
NOT A DANGEROUS GOOD
ACCORDING TO THE AUSTRALIAN
DANGEROUS GOODS (ADG) CODE
FOR TRANSPORT BY ROAD AND RAIL.

DIRECTIONS FOR USE

SITUATION	STATE	APPLICATION RATE	CRITICAL COMMENTS
General weedkilling sprays, High vol. power spray, Low vol. boom spray, Misting machines Knapsack	ALL STATES	10mL/100L 40mL/100L 5mL/5L 2mL/15L	
Reglone, High vol. power spray, Boom spray, Knapsack	ALL STATES	120mL/100L 120mL/100L 20mL/15L	For maximum efficiency of this herbicide a higher rate of TITAN Wetter 1000 must be used to ensure even and thorough coverage of plant foliage and to increase absorption. This is particularly important for killing grasses and tall, dense vegetation.
TITAN Paraquat 250 Herbicide, TITAN EOS Herbicide	ALL STATES	60mL/100L 120mL/100L	These formulations contain wetting agents and TITAN Wetter 1000 is only required if dilution rates are excessive, ie. low chemical rates and high water rates per ha. Consult product labels before using.
Tryquat* 200	ALL STATES	200mL/100L 100mL/100L	If volume of water applied when using 3-4L Tryquat 200 exceeds 200mL/ha. When using Tryquat 200 at 300-400mL/100L.
Fusilade*	ALL STATES	200mL/100L 120mL/100L	Use this rate unless otherwise specified on the Fusilade label. Some vegetables and ornamentals.
TITAN Diclofop-Methyl 375 Selective Herbicide	WA only	250mL/100L	Use TITAN Wetter 1000 at 250mL when mixing TITAN Diclofop-Methyl 375 Selective Herbicide with Homyx*, Tigrex*, or MCPA LVE. DO NOT add BS1000 with mixtures of TITAN Diclofop-Methyl 375 Selective Herbicide and Linuron, Bromoxynil or Methabenzthiazuron.
Soil Residual Herbicides eg. TITAN Diuron 900 WG, TITAN Atrazine 900 WG	ALL STATES	100-400mL/100L	When applying soil active herbicides such as TITAN Diuron 900 WG or TITAN Atrazine 900 WG to standing weeds, add TITAN Wetter 1000 to thoroughly wet foliage. Consult product labels for individual recommendations.
Fire fighting, Water tanker, Knapsack	ALL STATES	5 mL/100 L 2 mL/15 L	In this field, TITAN Wetter 1000 has the advantages of less weight to carry compared with less concentrated surfactants and of being non-flammable. It increases the wetting power of water which assists in quick control and mopping up of fires. It is of particular value where water may not be readily available as a less drenching spray is needed and a tankful will cover a bigger area.

NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.

GENERAL INSTRUCTIONS

TITAN Wetter 1000 is a biodegradable, non-ionic surfactant suitable for use with all types of herbicides, insecticides and fungicides.

It is suitable for application from properly calibrated boomsprayers, misting machines, aircraft and knapsacks.

Thorough coverage is essential but care should be taken to ensure run-off does not occur when using hand held equipment or knapsacks.

WEEDKILLING SPRAYS

TITAN Wetter 1000 should be added to all herbicide sprays to increase their efficiency except those which are known to contain adequate wetting agent in the formulation.

Wetter should be added only where directed on individual labels, as use with selective herbicides outside label directions may reduce crop selectivity.

For foliar active herbicides spray to the point where the leaves and stems are just wet. Spraying beyond this encourages runoff and subsequent loss of spray chemicals.

In general, use a high volume spray for soil residual herbicides. When spraying waxy or hairy leafed plants which are normally hard to wet, increased activity will be obtained by increasing the rate of TITAN Wetter 1000.

It is important that the leaves and stems are thoroughly wetted for foliar herbicides to work efficiently particularly when treating dense tall vegetation.

COMPATIBILITY

TITAN Wetter 1000 may be used with all products where the addition of a non-ionic wetting agent or surfactant is recommended.

MIXING

TITAN Wetter 1000 mixes easily with all types of water and should be added directly to the spray tank. It should not be added to undiluted sprays, concentrates or chemicals containing wetting agents. Add the wetter near the end of the filling process, to minimise foaming.

PROTECTION OF WILDLIFE, FISH, CRUSTACEANS AND ENVIRONMENT

Do not contaminate streams, rivers or waterways with the chemical (e.g. by spraying, cleaning equipment or disposal of waste), or with used containers.

STORAGE AND DISPOSAL

KEEP OUT OF REACH OF CHILDREN. Store in the closed original container in a cool, well-ventilated area. DO NOT store for prolonged periods in direct sunlight. Triple or preferable pressure rinse containers before disposal. Add rinsate to spray tank. DO NOT dispose of undiluted chemicals on-site. If recycling, replace cap and return clean containers to recycler or designated collection point. If not recycling, break, crush or puncture and bury empty containers in a local authority landfill. If no landfill is available, bury the containers below 500mm in a disposal pit specifically marked and set up for this purpose, clear of waterways, desirable vegetation and tree roots. Empty containers and product should not be burnt.

SAFETY DIRECTIONS

Avoid all eye and skin contact. Wear rubber/PVC gloves, goggles and overalls. If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre. Phone Australia 13 11 26. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

MATERIAL SAFETY DATA SHEET

Additional information is listed in the material safety data sheet (MSDS). A material safety data sheet for TITAN Wetter 1000 is available from TITAN AG Pty Ltd on request. Call Customer Service on (02) 9999 6655 or visit www.titanag.com.au

CONDITIONS OF SALE

TITAN AG Pty Ltd shall not be liable for any loss injury damage or death whether consequential or otherwise whatsoever or howsoever arising whether through negligence or otherwise in connection with the sale supply use or application of this product. The supply of this product is on the express condition that the purchaser does not rely on TITAN AG's skill or judgment in purchasing or using the same and every person dealing with this product does so at his own risk absolutely. No representative of TITAN AG Pty Ltd has any authority to add to or alter these conditions.

* Registered trademarks