

TITAN BESUTO 480

MIXING GUIDE


STEPS	FORMULATION/ ADDITIVE	PRODUCT EXAMPLES	INSTRUCTIONS
1	Water Total water volume of 70-100L/ha is recommended.		Add 70% of water requirement and maintain good agitation throughout the mixing process.
2	Conditioners	Companion, Liase, Crystalline ammonium sulphate.	Use these products to ameliorate water hardness, pH or aid in compatibility.
3	Dry Products Water dispersible granules (WG), Dry flowable (DF), Wettable powders (WP).	Triasulfuron, Sharpen, Diuron 900DF, Roundup Ready® Herbicide, Titan CC & Dry OTT Glyph Herbicide.	Add to the tank gradually, allowing at least 10 minutes for thorough dispersal.
4	Suspension Concentrates (SC)	Titan Besuto	Shake drums thoroughly prior to adding and rinse drums into the tank.
5	Emulsifiable Concentrates (EC)	Trifluralin, Tri-allate, Chlorpyrifos, Boxer Gold®, Prosulfocarb, 2,4-D LV Ester 680.	
6	Soluble Concentrates (SL) (Part A)	Amicide Advance®, Titan Amine 720, SpraySeed®, Kamba®, Lontrel Advanced®, Paraquat 250.	
7	Water		Fill to approx. 95% capacity.
8	Soluble Concentrates (SL) (Part B)	Roundup Ultramax®, Roundup Ready PL®.	
9	Adjuvants/Oils	BS1000®, Hasten®, Uptake®, Spray oil®, Titan Wetter 1000, Titan Duelling.	Add non-water conditioning adjuvants and oils last. Don't allow mixtures to stand unagitated. Add water to 100% of desired volume.

OTHER NOTES:

- High water rates aid product compatibility. Use a minimum water volume of 70L/ha.
- The use of 50 mesh (coarse) filters is recommended.
- The use of cold water may increase dispersion time.
- Do not let tank mixes stand unagitated.

DISCLAIMER: THIS IS NOT A COMPATIBILITY GUIDE. This is a mixing guide only. Please refer to compatibility guide on the product label. If unsure of compatibility, conduct a jar test with the same field ratios.



EXCLUSIVELY AVAILABLE FROM YOUR LOCAL  BRANCH

TITANAG.COM.AU

 **TITAN AG**
CROP PROTECTION